



Recycling for a better world

Data Sheet

VENEGREEN® PP100 Transparent

Product Description

- Recycling from coextruded transparent polypropylene (PP) films.
- Good mechanical properties.
- Good processability.
- Good rigidity.

Appearance

- Translucent appearance material.

Use:

- Injection of household goods, baskets, shovels, buckets and injection of general purpose articles. Each user must do validation test of the end use.



TECHNICAL SPECIFICATIONS			
PROPERTY	METHOD	UNITY	SPECIFICATION
MELT FLOW RATE (230°C)	ASTM D-1238	[g/10min]	5 - 11
ABSOLUTE DENSITY*	ASTM D-792	[g/cm ³]	0.905 - 0.915
NUMBER OF PELLETS PER GRAMO	-	[n.º pellet/g]	30 - 50

(*)Absolute density based on raw materials used

Storage Mode

- Indoor, to avoid the direct incidence of the sun's rays.
- Dry place (protected from humidity not greater than 60%).
- Maximum two pallets (one on top of another).
- Temperature not exceeding 30° C.



J-06001261-9

Calle 8 edif. El Morro, 3rd floor, La Urbina Caracas, Venezuela. Tlf +58 212 2412229 / planta San Juan +58 246 4312011 / fax +58 2464310607

The technical information provided herein is accurate and reliable to the best of our knowledge. It is obtained from the analyzes carried out in our laboratory of Quality Assurance under the indicated test methods and is of statistical character.